

TECHNICAL DATA SHEET

LAV LED IP67 Flex Led 4.8W


VERSION - 08.08.2016

STANDARD LUMINAIRE


Reference	LAV LED
Protection Class	IP67
Lighting Source	Flex Led 4.8W
Silicone	Silicone treatment IP67
Dimensions	16 x 11mm
Lenght Standard	140 - 540 - 1040 - 1540 - 2040 - 2540mm
Lenght on measure	on request up to 2940mm Cutable every 100mm
Nb Lighting Unit	60 LED/m
Voltage	24V
Power	4.8W/m
Power Cable	One side - 50cm Cable PUR 2x1mm ²
End Caps	EFA + EFA10



LAV LED / Flex Led 4.8W



ON REQUEST: LAV LED Fixation FCU



FINISH

Color Finishing Profil

Standard	Natural Anodised Aluminium
On request	Thermo-enameling Powder Coating RAL Color Anodising Polished Aluminium Chrome Aspect Polished Aluminium Gold Aspect

ON REQUEST: Connecting plug

AF/AMS



AF-E/AMS-E - IP68



ON REQUEST

Fixation	FCU (Ht: +4mm)
Power Cable	Both side - 50cm Cable PUR 2x1mm ²
Connecting Plug	AMS / AF or AMS-E / AF-E (IP68)
Dimming Option	1-10V, Dali, KNX <i>Ask technical departement for more information</i>

LIGHTING SOURCE

Lighting Source	Flex Led
Voltage	24V
Power	4.8W/m
Nb Led	60 LED/m - LED Pitch: 16.8mm
Beam Angle	120°
CRI	>80
Cut-Out	every 100mm
Lifetime	50'000h or 5 years
Working T°	-30°C to +75°C

Color Temperature & Luminous Flux / Meter

CCT	2700K	3000K	4000K
lm/m	129 lm	140 lm	166 lm

CERTIFICAT

